

工位数S	转位角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速度 N (rpm)								摩擦 扭力 Tx(kgf-m)
				50	100	150	200	300	400	500	700	
2	270	6D	4.34	1.41	1.15	1.02	0.93	0.83	0.76	0.71	0.64	0.22
3	180		4.34	1.70	1.38	1.22	1.12	0.99	0.91	0.85	0.77	0.22
	270		12.26	4.30	3.49	3.09	2.84	2.51	2.31	2.16	1.95	0.28
4	180		2.06	0.81	0.66	0.59	0.54	0.48	0.44	0.41		0.13
	270		5.42	1.90	1.54	1.36	1.25	1.11	1.02	0.95	0.86	8.18
5	180		1.76	0.69	0.56	0.50	0.45	0.40	0.37	0.35		0.1
	270		2.37	0.84	0.68	0.61	0.56	0.49	0.45	0.42	0.38	0.11
6	90		4.34	2.32	1.88	1.67	1.53	1.35	1.24	1.16		0.22
	120		11.69	5.77	4.83	4.27	3.92	3.47	3.18	2.98	2.69	0.3
	150		12.73	5.80	4.71	4.17	3.83	3.39	3.11	2.91	2.63	0.27
	180		13.43	5.64	4.58	4.06	3.72	3.30	3.02	2.83	2.56	0.26
	210		13.91	5.48	4.45	3.94	3.62	3.20	2.94	2.75	2.48	0.25
	240		14.25	5.33	4.33	3.83	3.52	3.11	2.86	2.67	2.42	0.24
	270		14.5	5.19	4.22	3.73	3.42	3.03	2.78	2.60	2.35	0.23
	300		14.68	5.06	4.11	3.64	3.34	2.96	2.71	2.54	2.29	0.23
330	14.82		4.94	4.01	3.55	3.26	2.89	2.65	2.48	2.24	0.22	
8	90		2.06	1.11	0.90	0.80	0.73	0.65	0.60	0.56		0.09
	120		5.29	2.65	2.15	1.91	1.75	1.55	1.42	1.33	1.20	0.18
	150		5.52	2.53	2.06	1.82	1.67	1.48	1.36	1.27	1.15	0.17
	180		5.66	2.43	1.97	1.75	1.60	1.42	1.30	1.22	1.10	0.17
	210		5.75	2.33	1.90	1.68	1.54	1.36	1.25	1.17	1.06	0.16
	240		5.81	2.25	1.83	1.62	1.49	1.32	1.21	1.13	1.02	0.26
	270		5.85	2.18	1.77	1.57	1.44	1.28	1.17	1.09	0.99	0.16
	300		5.88	2.12	1.72	1.53	1.40	1.24	1.14	1.06	0.96	0.15
330	5.9		2.07	1.68	1.49	1.36	1.21	1.11	1.04	0.94	0.15	
10	90		1.76	0.94	0.76	0.68	0.62	0.55	0.50	0.47		0.1
	120		2.33	1.18	0.96	0.85	0.78	0.69	0.63	0.59		0.12
	150		2.4	1.12	0.91	0.81	0.74	0.65	0.60	0.56	0.51	0.11
	180		2.44	1.07	0.87	0.77	0.71	0.63	0.57	0.54	0.48	0.11
	210		2.47	1.03	0.83	0.74	0.68	0.60	0.55	0.51	0.47	0.11
	240		2.49	0.99	0.80	0.71	0.65	0.58	0.53	0.50	0.45	0.06
	270		2.5	0.96	0.78	0.69	0.63	0.56	0.51	0.48	0.43	0.1
	300		2.51	0.93	0.76	0.67	0.61	0.54	0.50	0.47	0.42	0.1
330	2.51	0.90	0.73	0.65	0.60	0.53	0.48	0.45	0.41	0.1		
12	90	0.94	0.49	0.40	0.35	0.32	0.29	0.26			0.09	
	120	1.91	0.96	0.78	0.69	0.63	0.56	0.51	0.48	0.43	0.09	
	150	1.95	0.91	0.74	0.65	0.60	0.53	0.49	0.45	0.41	0.09	
	180	1.97	0.86	0.70	0.62	0.57	0.50	0.46	0.43	0.39	0.09	
	210	1.99	0.83	0.67	0.60	0.55	0.48	0.44	0.41	0.37	0.09	
	240	2	0.80	0.65	0.57	0.53	0.47	0.43	0.40	0.36	0.09	
	270	2.01	0.77	0.63	0.55	0.51	0.45	0.41	0.39	0.35	0.09	
	300	2.01	0.75	0.61	0.54	0.49	0.44	0.40	0.37	0.34	0.09	
330	2.01	0.73	0.59	0.52	0.48	0.42	0.39	0.36	0.33	0.2		

工位数S	转位角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速度 N (rpm)							摩擦 扭力 Tx(kgf-m)			
				50	100	150	200	300	400	500		700		
16	90*	6D	2.06	1.11	0.90	0.80	0.73	0.65			0.13			
	120*		5.29	2.65	2.15	1.91	1.75	1.55	1.42	1.33	1.20	0.18		
	150*		5.52	2.53	2.06	1.82	1.67	1.48	1.36	1.27	1.15	0.17		
	180*		5.66	2.43	1.97	1.75	1.60	1.42	1.30	1.22	1.10	0.17		
	210*		5.75	2.33	1.90	1.68	1.54	1.36	1.25	1.17	1.06	0.16		
	240*		5.81	2.25	1.83	1.62	1.48	1.32	1.21	1.13	1.02	0.16		
	270*		5.85	2.18	1.77	1.57	1.44	1.28	1.17	1.09	0.99	0.16		
	300*		5.88	2.12	1.72	1.53	1.40	1.24	1.14	1.06	0.96	0.15		
	330*		5.9	2.07	1.68	1.49	1.36	1.21	1.11	1.04	0.94	0.15		
20	90*		1.76	0.94	0.76	0.68	0.62	0.55			0.1			
	120*		2.33	1.18	0.96	0.85	0.78	0.69	0.63	0.59	0.12			
	150*		2.4	1.12	0.91	0.81	0.74	0.65	0.60	0.56	0.11			
	180*		2.44	1.07	0.87	0.77	0.71	0.63	0.57	0.54	0.48	7.8		
	210*		2.47	1.03	0.83	0.74	0.68	0.60	0.55	0.51	0.47	0.11		
	240*		2.49	0.99	0.80	0.71	0.65	0.58	0.53	0.50	0.45	0.11		
	270*		2.5	0.96	0.78	0.69	0.63	0.56	0.51	0.48	0.43	0.11		
	300*		2.51	0.93	0.76	0.67	0.61	0.54	0.50	0.47	0.42	0.11		
	330*		2.51	0.90	0.73	0.65	0.60	0.53	0.48	0.45	0.41	0.11		
24	90*		0.94	0.49	0.40	0.35	0.32	0.29			0.09			
	120*		0.98	0.46	0.37	0.33	0.30	0.27	0.25			0.09		
	150*		1.95	0.91	0.74	0.65	0.60	0.53	0.49	0.45			0.09	
	180*		1.97	0.86	0.54	0.62	0.57	0.50	0.46	0.7			0.09	
	210*		1.99	0.83	0.67	0.60	0.55	0.48	0.44	0.41	0.37			0.09
	240*		2	0.80	0.65	0.57	0.53	0.47	0.43	0.40	0.36			0.09
	270*		2.01	0.77	0.63	0.55	0.51	0.45	0.41	0.39	0.35			0.09
	300*		2.01	0.75	0.61	0.54	0.49	0.44	0.40	0.37	0.34			0.09
	330*		2.01	0.73	0.59	0.52	0.48	0.42	0.39	0.36	0.33			0.09
30	90●		1.76	0.94	0.76	0.68	0.62	0.55	0.50	0.47			0.1	
	120●		2.33	1.18	0.93	0.49	0.78	0.69	0.63	0.59	0.54			0.12
	150●		2.4	1.12	0.91	0.81	0.74	0.65	0.60	0.56	0.51			0.11
	180*	2.44	1.07	0.87	0.77	0.71	0.63	0.57	0.54	0.48			0.11	
	210●	2.47	1.03	0.83	0.74	0.68	0.60	0.55	0.51	0.47			0.11	
	240●	2.49	0.99	0.80	0.71	0.65	0.58	0.53	0.50	0.45			0.11	
	270●	2.5	0.96	0.78	0.69	0.63	0.56	0.51	0.48	0.43			0.1	
	300●	2.51	0.93	0.76	0.67	0.61	0.54	0.50	0.47	0.42			0.1	
	330●	2.51	0.90	0.73	0.65	0.60	0.53	0.48	0.45	0.41			0.1	

备注：○：1DWELL *：2DWELL ●：3DWELL ☆：4DWELL