

工位数S	转位 角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速度 N (rpm)						摩擦 扭力 Tx(kgf-m)	
				50	100	150	200	300	400		500
4	270	8DT	30.5	11.3	9.7	8.1	7.3	6.1	5.2	0.9	
	300		32.1	11.0	9.4	7.9	7.0	5.8	5.0	0.9	
	330		35.6	10.7	9.4	7.6	6.8	5.6	5.0	0.9	
5	180		21.5	7.3	6.0	5.1	4.2	4.0		0.9	
	210		22.7	7.3	6.0	5.0	4.0	3.8		0.7	
	240		25.2	8.5	7.1	6.2	5.1			0.7	
	270		26	8.1	6.5	5.8	5.5	4.8		0.7	
	300		27.8	8.0	6.4	5.7	5.0	4.5		0.7	
	330		28.3	7.9	6.4	5.6	4.9	4.3		0.7	
6	180		23.1	7.7	6.2	5.4	4.6	4.1		0.7	
	210		24.2	7.7	6.0	5.3	4.4	4.0		0.7	
	240		25	7.4	6.0	5.3	4.4	4.0		0.7	
	270		27.2	8.4	7.0	6.2	5.7	5.0		0.7	
	300		28.9	8.1	6.8	6.0	5.4	4.7		0.7	
	330		29.7	8.0	6.6	5.7	4.9	4.5		0.7	
8	150		32.1	14.7	11.9	10.5	9.7	8.6	7.9		0.8
	180		33.4	16.8	14.2	13.1	11.5	10.5	9.1		0.8
	210		37.1	15.2	13.6	12.6	12.0	10.0	8.1		0.8
	240		38.9	14.8	13.1	12.5	11.7	9.2	7.6		0.8
	270		41	14.3	12.8	12.1	11.0	8.8	7.0		0.8
	300		43.5	13.8	12.1	11.6	10.5	8.1	6.5		0.8
	330		45.1	13.4	11.2	10.3	9.7	7.7	5.9		0.8
10	150		24	7.8	6.5	5.6	4.6	4.4	4.0		0.7
	180		26.1	8.1	6.7	5.6	4.5	4.5	4.1		0.7
	210		30.1	9.2	7.6	6.6	5.9	5.4	4.6		0.7
	240		33.7	8.8	7.5	6.4	5.7	5.2	4.4		0.7
	270		35.2	8.6	7.3	6.2	5.5	5.0	4.1		0.7
	300	36.5	8.4	7.1	6.0	5.3	4.8	3.9		0.7	
	330	38.1	8.1	6.9	5.7	4.9	4.3	3.6	0.7	0.7	
12	150	22.1	8.0	6.2	5.8	4.9	4.5	3.7		0.6	
	180	23.5	8.5	6.8	6.0	5.2	4.8			0.6	
	210	29	8.2	6.8	6.1	5.2	4.8	4.1		0.6	
	240	30.2	8.3	6.5	5.7	4.9	4.2	3.8		0.6	
	270	31.5	9.2	8.0	7.1	6.3	5.6	4.3		0.6	
	300	32.7	8.4	6.7	5.9	5.1	4.4	4.0		0.6	
	330	33.2	8.2	6.4	5.3	4.8	4.0	3.6		0.6	
15	90	17	4.8	3.1	2.0	1.6	1.2	1.0		0.6	
	120	18.1	5.1	3.3	2.3	1.8	1.3	1.1		0.6	
	150	18.9	5.4	3.5	2.6	2.1	1.6	1.3		0.6	
	180	23.2	6.8	5.0	3.7	3.1	2.7	2.4		0.6	
	210	24.5	6.7	4.8	3.8	3.0	2.5	2.0		0.6	
	240	26.1	6.8	4.8	3.7	3.1	2.4	2.2		0.6	
	270	27.5	7.2	5.3	4.4	3.4	2.7	2.4		0.6	

工位数S	转位 角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速度 N (rpm)						摩擦 扭力 Tx(kgf-m)
				50	100	150	200	300	400	
15	300	8DT	28.1	7.5	5.5	4.5	3.6	2.8	2.5	0.6
	330		28.7	7.5	5.6	4.4	3.5	2.7	2.4	0.6
16	90		16.2	4.1	3.0	2.2	1.4	0.9	0.7	0.6
	120		16.4	4.3	3.1	2.3	1.5	1.0	0.8	0.6
	150		16.4	4.5	3.3	2.4	1.8	1.3	1.0	0.6
	180		20.2	5.2	3.5	2.5	1.9	1.4	1.1	0.6
	210		21	5.5	3.6	2.7	2.0	1.6	1.3	0.6
	240		22.1	5.5	3.6	2.7	2.0	1.7	1.2	0.6
	270		22.9	5.6	4.9	1.9	1.9	1.5	1.0	0.6
	300		23.2	5.6	3.8	2.7	1.8	1.6	1.1	0.6
	330		23.4	5.7	3.9	2.8	1.8	1.5	1.0	0.6
	20		*90	19	6.2	4.8	3.9	3.0	2.6	2.0
*120			20.5	6.4	5.0	4.2	3.3	2.9	2.3	0.7
*150			24	7.8	6.5	5.6	4.6	4.4	4.0	0.7
*180			26.1	8.1	6.7	5.6	4.5	4.5	4.1	0.7
*210			30.1	9.2	7.6	6.6	5.9	5.4	4.6	0.7
*240			33.7	8.8	7.5	6.4	5.7	5.2	4.4	0.7
*270			35.2	8.6	7.3	6.2	5.5	5.0	4.1	0.7
*300			36.5	8.4	7.1	6.0	5.3	4.8	3.9	0.7
24	*330		38.1	8.1	6.9	5.7	4.9	4.3	3.6	0.3
	*90	18.2	4.9	3.1	2.2	1.7			0.4	
	*120	18.2	5.0	3.1	2.3	1.8			0.3	
	*150	22.1	8.0	6.2	5.8	4.9	4.5	3.7	0.3	
	*180	23.5	8.5	6.8	6.0	5.2	4.8	4.1	0.4	
	*210	29	8.2	6.8	6.1	5.2	4.8	4.1	0.4	
	*240	30.2	8.3	6.5	5.7	4.9	4.2	3.8	0.4	
	*270	31.5	9.2	8.0	7.1	6.3	5.8	4.3	0.3	
	*300	32.7	8.4	6.7	5.9	5.1	4.4	4.0	0.3	
30	*330	33.2	8.2	6.4	5.3	4.8	4.0	3.6	0.3	
	*90	17	4.8	3.1	2.0	1.6	1.2	1.0	0.7	
	*120	18.1	5.1	3.3	2.3	1.8	1.3	1.1	0.6	
	*150	18.9	5.4	3.5	2.6	2.1	1.6	1.3	0.6	
	*180	23.2	6.8	5.0	3.7	3.1	2.7	2.4	0.6	
	*210	24.5	6.7	4.8	3.8	3.0	2.5	2.0	0.6	
	*240	26.1	6.8	4.8	3.7	3.1	2.4	2.2	0.6	
	*270	27.5	7.2	5.3	4.4	3.4	2.7	2.4	0.6	
	*300		7.5	5.5	5.4	3.6	2.8	2.5	0.6	
	*330	28.7	7.5	5.6	4.4	3.5	2.7	2.4	0.6	
32	90*	16.2	4.1	3.0	2.2	1.4	0.9	0.7	0.6	
	120*	16.4	4.3	3.1	2.3	1.5	1.0	0.8	0.6	
	150*	16.4	4.5	3.3	2.4	1.8	1.3	1.0	0.6	
	180*	20.2	5.2	3.5	2.5	1.9	1.4	1.1	0.6	
	210*	21	5.5	3.6	2.7	2.0	1.6	1.3	0.6	

工位数S	转位 角度	规格	静扭力 Ts (kgf-m)	动扭力 (kgf-m) 分割回转速度 N (rpm)						摩擦 扭力 Tx(kgf-m)	
				50	100	150	200	300	400		500
32	240*	8DT	22.1							0.6	
	270*		22.9	5.6	4.9	12.6	1.9	1.5	1.0	0.6	
	*300		23.2	5.6	3.8	2.7	1.8	1.6	1.1	0.6	
	*330		23.4	5.7	3.9	2.8	1.8	1.5	1.0	0.6	
	90☆		19	6.2	4.8	3.9	3.0	2.6	2.0	0.7	
	120☆		20.5	6.4	5.0	4.2	3.3	2.9	2.3	0.7	
	150☆		24	7.8	6.5	5.6	4.6	4.4	4.0	0.7	
	180☆		26.1	8.1	6.7	5.6	4.5	4.5	4.1	0.7	
	210☆		30.1	9.2	7.6	6.6	5.9	5.4	4.6	0.7	
	240☆		33.7	8.8	7.5	6.4	5.7	5.2	4.4	0.7	
	270☆		35.2	8.6	7.3	6.2	5.5	5.0	4.1	0.7	
	300☆		36.5	8.4	7.1	6.0	5.3	4.8	3.9	0.7	
	330☆		38.1	8.1	6.9	5.7	4.9	4.3	3.6	0.7	
40	90☆		18.2	4.9	3.1	2.2	1.7			0.6	
	120☆		18.2	5.0	3.1	2.3	1.8			0.3	
	150☆		22.1	8	6.2	5.8	4.9	4.5	3.7	0.3	
	180☆		23.5	8.5	6.8	6.0	5.2	4.8	4.1	0.4	
	210☆		29	8.2	6.8	6.1	5.2	4.8	4.1	0.6	
	240☆		30.2	8.3	6.5	5.7	7.2	4.9	4.2	3.8	0.6
	270☆		31.5	9.2	8.0	6.9	6.4	5.6	4.3	3.8	0.6
	300☆		32.7	8.4	6.7	6.3	5.8	4.4	4.0	3.6	0.6
	330☆		33.2	8.2	6.4	6.1	6.0	4.0	3.6		0.6
48											
60											
80											

备注： ○：1DWELL *：2DWELL ●：3DWELL ☆：4DWELL